

# YOUR POS TOUCH TERMINAL



CORIS  TECH  
affidabilità innovazione tecnologia



# YOUR POS

## Model yourPOS FANLESS

|                |   |
|----------------|---|
| Processor      | Intel® Atom™ D525, 1M L2 Cache 1.8Ghz   |
| System Memory  | 2GB, Maximum 4GB (1x204-pin DDR3)       |
| Power Supply   | 90W (12V / 12.5A) External Power Supply |
| Storage Device | SSD 60 GB                               |
| Graphics       | Intel® GMA 3150                         |
| Speaker        | Internal Speaker 2W x 2                 |
| Construction   | Aluminum Die-casting + Plastic + Glass  |
| Housing Color  | Black with Silver Trim                  |

## Touch LCD Display

|  |   |
|--|---|
| Size / Resolution                          | 15" TFT-LCD/ 1024 X 768   |
| Brightness (Backlight Type) & Touch Screen | 250 cd/m2 (CCFL); 5-Wire Resistive Touch<br>350 cd/m2 (LED) with Tempered Glass; Projected Capacitive Touch (SU ORDINAZIONE PER QUANTITA' ) |

## I/O Ports

|                  |  |
|------------------|--|
| Serial Port      | 3 x External: COM1, COM2 (DB9), COM4 (RJ-45) |
| USB Port         | 5 x External (4 Rear + 1 Side)               |
| Cash Drawer Port | 1 x RJ11 (12V)                               |
| Printer Port     | 1 x Bi-directional Parallel port             |
| Keyboard / Mouse | 1 x PS/2                                     |
| LAN Port         | 1 x RJ45 Giga LAN                            |
| Audio Port       | 1 x Line Out                                 |
| VGA Port 1 x VGA | 1 x VGA                                      |
| DC Output        | 1 x 12V DC Jack 2.5 mm                       |

## Optional I/O Board

|        |                                  |
|--------|----------------------------------|
| Type A | Serial Port: COM3 & COM5 (RJ-45) |
|--------|----------------------------------|

## OS Supported

|         |   |
|---------|---|
| Windows | POSReady 2009 incluso, POSReady 7 a richiesta |
|---------|---|

## Physical Dimensions

|                    |                    |
|--------------------|--------------------|
| Dimensions (WxHxD) | 367 x 352 x 223 mm |
|--------------------|--------------------|

## Environment

|                       |                           |
|-----------------------|---------------------------|
| EMI / Safety          | CE, FCC Class A           |
| Operating Temperature | 0°C ~ 40°C (32°F ~ 104°F) |

## Optional Peripherals

|                             |   |
|-----------------------------|---|
| Magnetic Stripe Card Reader | Integrated MCR Module (Single / Dual / Triple Track Selectable) |
| 2nd Monitor                 | Integrated 11.6" or 15" Pole-type LCD Display                   |
| Customer Display            | Integrated LCM / VFD Customer Display                           |
| Wireless LAN                | Integrated 802.11 b/g/n Wireless Module                         |
| Identification Devices      | RFID 13.56 MHz / Fingerprint Reader / i-Button                  |

